

FSWP-300 CONC 3" 1.3125" 3.6875" 2.25" 2.375" FE2604

NOTE:

ARCHITECT/CONTRACTOR NOTE: ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED

The Smoke Barrier application shown uses non-permeable stainless steel foil identical to those cited in the Air Leakage Test Summary Letter dated June 30, 2003. Suitability for use and approval of these components for Smoke Barrier applications shall be by the authority having jurisdiction (AHJ).

	Approved by:	Date:
	SEAL NOTE: SPECIFY SEAL COLOR	
	STANDARD COLORS: CARBON (BLACK)	PRAIRIE (BEIGE
	FOG (GRAY)	LUNAR (WHITE)
*CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF. CONTACT MM FOR PRICING & AVAILABILITY.		IMUM QUANTITIES 100 LF. LABILITY.

07-25-14

Project: Location: Project Number Representative: Customer: RIGHTS OF DESIGN 50 MM WAY FSWP-300_CONC_SMOKE BARRIER All rights of design, detail, engineering and/or PENDERGRASS, GA. 30567 invention contained herein are the property of MM PHONE: 706-824-7500 Systems Corporation and herby reserved and are not to 800-241-3460 Drawn by: Drawing Number MM SYSTEMS Scale: be reproduced or provided to any other party. MM FAX: 706-824-7501 LMP Systems Corporation reserves the right to amend or NTS FE2604 withdraw any information contained herein without Issue Date:

notice and will not be liable for any inaccuracy or

ambiguity of said information.

SHT. . OF .

www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

^{*} NOTE THAT SEALS DISENGAGE FROM FRAME AFTER THERMAL MIN AND THERMAL MAX.