

<sup>\*</sup> NOTE THAT SEALS DISENGAGE FROM FRAME AFTER THERMAL MIN AND THERMAL MAX.

## NOTE:

ARCHITECT/CONTRACTOR NOTE: ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative:

The Smoke Barrier application shown uses non-permeable stainless steel foil identical to those cited in the Air Leakage Test Summary Letter dated June 30, 2003. Suitability for use and approval of these components for Smoke Barrier applications shall be by the authority having jurisdiction.

Approved by:	Date:
SEAL NOTE: SPEC	JIFY SEAL COLOR
STANDARD COLORS:  CARBON (BLACK)	PRAIRIE (BEIGE
FOG (GRAY)	LUNAR (WHITE)
*CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF. CONTACT MM FOR PRICING & AVAILABILITY.	

<b>A</b>	MM
	MM SYSTEMS

Customer:

Project:

Location:

Project Number

RIGHTS OF DESIGN 50 MM WAY PENDERGRASS, GA. 30567

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

FSWPL-300\_CONC\_SMOKE BARRIER

Drawing Number Drawn by: Scale: LMP NTS Issue Date: SHT. . OF . 07-25-14

FE2704

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

FAX:

PHONE: 706-824-7500

800-241-3460

706-824-7501

www.mmsystemscorp.com