

1/4" - 20 X 1 1/2" FHMS/SS

@ 24" O.C. [610mm]

IMPORTANT LIFE SAFETY PRODUCT NOTE PF-2018F-SC-7-3.5 (OPTIONAL) TO ACHIEVE RATING, 2-HOUR FIRE BARRIER

MUST BE INSTALLED IN 2-HOUR RATED SLAB, MINIMUM 4-1/2" JT. FACE. BARRIERS MUST BE INSTALLED IN STRICT ACCORDANCE WITH TYPICAL FLOOR FIRE BARRIER INSTALLATION INSTRUCTIONS PROVIDED IN THIS SUBMITTAL.

* CONTACT FACTORY FOR OTHER SYLES OF FIRE BARRIEF

	Nominal	Joint Opening "JT"			Total	Mat.	
Model	"JT"	Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.	Movement	Code
FDT-70025R	7"	1.875"	6"	8"	9.5"	7.625"	FD1317
FDT-70025R w/ PF-2018F-SC-7-3.5	7"	3.5"	6"	8"	9.5"	6"	FD1317

^{*} NOTE THAT SEALS DISENGAGE FROM FRAME AT SEISMIC MIN AND SEISMIC MAX.

ARCHITECT/CONTRACTOR NOTE:

ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative:

Approved by: Date: SEAL NOTE: SPECIFY SEAL COLOR CARBON (BLACK) PRAIRIE (BEIGE) LUNAR (WHITE) FOG (GRAY) CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF. Project Number

MM SYSTEMS

Customer:

Project:

Location:

FDT-700-.25R

50 MM WAY PENDERGRASS, GA. 30567 PHONE: 706-824-7500 800-241-3460 FAX: 706-824-7501

www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and herby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Model: Drawn by: Scale:

LMP NTS Issue Date: SHT. OF 06-30-11 Drawing Number: FD1317