


Model	Nominal "JT"	Joint Opening "JT"			Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Max.		
RXH-8-4	8"	.25"	4"	12"	11.75"	

NOTE THAT WHEN THE OPTIONAL FIRE BARRIER IS SELECTED THE MINIMUM JOINT OPENING WILL BE LARGER THAN SHOWN IN TABLE.

FIRE BARRIER (WHERE REQUIRED)
NOTE THAT FIRE BARRIER MUST BE FASTENED TO MASONRY AND NOT WOOD.

Representative: _____ Customer: _____ Project: _____ Location: _____ Project Number: _____



MM
SYSTEMS

50 MM WAY
PENDERGRASS, GA. 30567
PHONE: 706-824-7500
866-50 MM WAY
866-506-6929
FAX: 706-824-7501
www.mmssystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Model:

RXH-8-4

Drawn by:

SHT. . OF .

Scale:
NTS

Drawing Number:

Issue Date:
12-12-06