



IMPORTANT LIFE SAFETY NOTE
 4-1/2" MINIMUM REQUIRED FOR RATING ARCHITECT / CONTRACTOR MUST VERIFY PRIOR TO FABRICATION

IMPORTANT LIFE SAFETY PRODUCT NOTE
 PF-2019F-SC- (OPTIONAL)
 TO ACHIEVE RATING, 2-HOUR FIRE BARRIER MUST BE INSTALLED IN 2-HOUR RATED SLAB. MINIMUM 4-1/2" JT. FACE. BARRIERS MUST BE INSTALLED IN STRICT ACCORDANCE WITH ALL INSTALLED IN STRICT ACCORDANCE WITH ALL INSTRUCTIONS PROVIDED IN THIS SUBMITTAL.
 * CONTACT FACTORY FOR OTHER SIZES OF FIRE BARRIER

Model	Nominal "JT"	Joint Opening "JT"			Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.		
LASB-14-7	14"	7"	10.5"	17.5"	21"	14"
LASB-14-7 w/ PF-2248CF-SC-14-7	14"	7"	10.5"	17.5"	21"	14"

Representative: _____ Customer: _____ Project: _____ Location: _____ Project Number: _____

MM SYSTEMS
 50 MM WAY
 PENDERGRASS, GA. 30567
 PHONE: 706-824-7500
 866-50 MM WAY
 866-506-6929
 FAX: 706-824-7501
 www.mmsystemscorp.com

RIGHTS OF DESIGN
 All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

Model: **LASB-14-7**

Drawn by: LMP Scale: NTS

SHT. . OF . Issue Date: 01-30-09

Drawing Number: _____

For Spec-Data, Installation Guides, or movement requirements, contact MMISC