


IMPORTANT LIFE SAFETY NOTE
 THICKNESS AND CONSTRUCTION TO
 HOURLY ENDURANCE REQUIRED.
 PER IBC TABLE 721.2.2.1 "MINIMUM
 THICKNESS".

IMPORTANT LIFE SAFETY PRODUCT NOTE
 PF-2018F-SC-11-5.5 (OPTIONAL)
 TO ACHIEVE RATING, 2-HOUR FIRE BARRIER
 WHOSE JOINT FACE IS RATED FOR 2-HOUR.
 BARRIERS MUST BE INSTALLED IN STRICT
 ACCORDANCE WITH TYPICAL FLOOR FIRE
 BARRIER INSTALLATION INSTRUCTIONS
 PROVIDED IN THIS SUBMITTAL.
INTERTEK DESIGN NO. MME/JH 120-01

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
LASME-11-5.5	11"	0.0"	8.25"	13.75"	16.5"	16.5"	
LASME-11-5.5 w/ PF-2018F-SC-11-5.5	11"	3.5"	8.25"	13.75"	16.5"	13"	

USE WITH LASM-11-11

ARCHITECT/CONTRACTOR NOTE:
 ALL SUBASSEMBLY COMPONENTS TO BE
 PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS
 UNLESS OTHERWISE NOTED. THE SPECIFIC
 SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative:	Customer:	Project:	Location:	Project Number:	
 MM SYSTEMS 50 MM WAY PENDERGRASS, GA. 30567 PHONE: 706-824-7500 800-241-3460 FAX: 706-824-7501 www.mmsystemscorp.com		RIGHTS OF DESIGN All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.		<h1>LASME-11-5.5</h1>	
Model:		Drawn by:	Scale:	Drawing Number:	
		LMP	NTS		
SHT. . OF .		Issue Date:			
		04-15-15			