


IMPORTANT LIFE SAFETY NOTE
 NOTE 2 BARRIERS REQUIRED.
 MINIMUM WALL DEPTH REQUIRED FOR RATING:
 16" FOR SINGLE SIDE INSTALLATION (SHOWN).
 ARCHITECT / CONTRACTOR MUST VERIFY PRIOR TO
 FABRICATION

IMPORTANT LIFE SAFETY PRODUCT NOTE
 PF-2148CW-SC-14-14
 TO ACHIEVE RATING, 2-HOUR FIRE BARRIER
 MUST BE INSTALLED IN 2-HOUR RATED WALL.
 BARRIERS MUST BE INSTALLED IN STRICT
 ACCORDANCE WITH TYPICAL WALL FIRE
 BARRIER INSTALLATION INSTRUCTIONS
 PROVIDED IN THIS SUBMITTAL.
 INTERTEK DESIGN NO. MM/EJV 120-11

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
ASC-14-14_STUD_2HWPF_SS	14"	2.5"	10.5"	17.5"	28	25.5"	EJSW2023

SIGHT LINE MATCHES UP WITH ASCL-14-7 CLEAR ANODIZE IS STANDARD FINISH

Representative:	Customer:	Project:	Location:	Project Number:
-----------------	-----------	----------	-----------	-----------------



MM
 MM SYSTEMS
 50 MM WAY
 PENDERGRASS, GA. 30567
 PHONE: 706-824-7500
 800-241-3460
 FAX: 706-824-7501
 www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN
 All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

ASC-14-14_STUD_2HWPF_SS
 Model:

Drawn by: LMP	Scale: NTS	Drawing Number: EJSW2023
SHT. . OF .	Issue Date: 07-28-15	