

IMPORTANT LIFE SAFETY NOTE
NOTE 2 BARRIERS REQUIRED.
MINIMUM WALL DEPTH REQUIRED FOR RATING:
11.625" FOR SINGLE SIDE INSTALLATION (SHOWN)
ARCHITECT / CONTRACTOR MUST VERIFY PRIOR
TO FABRICATION


IMPORTANT LIFE SAFETY PRODUCT NOTE
PF-2018CW-SC-12-6
TO ACHIEVE RATING, 2-HOUR FIRE BARRIER
MUST BE INSTALLED IN 2-HOUR RATED WALL.
BARRIERS MUST BE INSTALLED IN STRICT
ACCORDANCE WITH TYPICAL WALL FIRE
BARRIER INSTALLATION INSTRUCTIONS
PROVIDED IN THIS SUBMITTAL.
INTERTEK DESIGN NO. MM/EJV 120-03

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
CRSL-12-6_STUD_2HWPF_SS	12"	6"	9"	15"	18"	12"	

USE WITH CRS-12-12

CLEAR ANODIZE IS STANDARD FINISH

Representative: _____ Customer: _____ Project: _____ Location: _____ Project Number: _____



MM SYSTEMS
50 MM WAY
PENDERGRASS, GA. 30567
PHONE: 706-824-7500
800-241-3460
FAX: 706-824-7501
www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN
All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

CRSL-12-6_STUD_2HWPF_SS
Model:
Drawn by: DAL
Scale: NTS
Issue Date: 01-10-17
Drawing Number: **EJSW2711**
SHT. . OF .