

Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
VSS-1832-E	18"	7.125"	13.5"	22.5"	36"	28.875"	VS1022

NOTE THAT EXTERIOR SEAL DISENGAGES AT 28". THE INTERIOR SEAL REMAINS INTACT UP TO 36".

Approved by: _____ Date: _____

SEAL NOTE: SPECIFY SEAL COLOR


STANDARD COLORS:

<input type="checkbox"/> CARBON (BLACK)	<input type="checkbox"/> PRAIRIE (BEIGE)
<input type="checkbox"/> FOG (GRAY)	<input type="checkbox"/> LUNAR (WHITE)

*CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF. CONTACT MM FOR PRICING & AVAILABILITY.

ARCHITECT/CONTRACTOR NOTE:
ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative:	Customer:	Project:	Location:	Project Number:
-----------------	-----------	----------	-----------	-----------------



MM SYSTEMS
50 MM WAY
PENDERGRASS, GA. 30567
PHONE: 706-824-7500
800-241-3460
FAX: 706-824-7501

www.mmsystemscorp.com

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

VSS-1832-E

Model:	Scale:	Drawing Number:
Drawn by: LMP	NTS	VS1022
SHT. . OF .	Issue Date: 02-09-11	