

ambiguity of said information.

NOTE THAT EXTERIOR SEAL WILL DISENGAGE IF MOVEMENT EXCEEDS THERMAL MAXIMUM BUT WATER-TIGHTNESS WILL BE MAINTAINED BY INTERIOR SEAL UP TO SEISMIC MAXIMUM

VSS-800-E CONC

ARCHITECT/CONTRACTOR NOTE:

ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

Approved by: Date: SEAL NOTE: SPECIFY SEAL COLOR CARBON (BLACK) PRAIRIE (BEIGE) ☐FOG (GRAY) LUNAR (WHITE) *CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF. CONTACT MM FOR PRICING & AVAILABILITY.

Project Number:

Drawing Number:

VS1007

12"

VW1007

03-02-12

SYSTEMS DICTATE THE LENGTHS PROVIDED.		D.				*CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITI CONTACT MM FOR PRICING & AVAILABILITY.	
Representative:	Custo	mer:	Project:	Location:		Project Number	
	M M	50 MM WAY PENDERGRASS, GA. 30567 PHONE: 706-824-7500 800-241-3460	RIGHTS OF DESIGN All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not	Model: VSS	S-800-E_0	CONC	
	MM SYSTEMS	FAX: 706-824-7501	to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or	Drawn by: LMP	Scale: NTS	Drawing Num	
	www.mmsystemscorp.com		withdraw any information contained herein without notice and will not be liable for any inaccuracy or	SHT OF .	Issue Date:	7 VS10	