



Model	Nominal "JT"	Joint Opening "JT"				Total Movement	Mat. Code
		Seismic Min.	Thermal Min.	Thermal Max.	Seismic Max.		
VSS-2554-I	25"	12"	18.75"	31.25"	50"	38"	

NOTE THAT EXTERIOR SEAL DISENGAGES AT 37".

Approved by: \_\_\_\_\_ Date: \_\_\_\_\_

**SEAL NOTE: SPECIFY SEAL COLOR**

STANDARD COLORS:

<input type="checkbox"/> CARBON (BLACK)	<input type="checkbox"/> PRAIRIE (BEIGE)
<input type="checkbox"/> FOG (GRAY)	<input type="checkbox"/> LUNAR (WHITE)

\*CUSTOM COLOR AVAILABLE IN MINIMUM QUANTITIES 100 LF. CONTACT MM FOR PRICING & AVAILABILITY.

**ARCHITECT/CONTRACTOR NOTE:**  
 ALL SUBASSEMBLY COMPONENTS TO BE PROVIDED IN 10'-0" OR 20'-0" STOCK LENGTHS UNLESS OTHERWISE NOTED. THE SPECIFIC SYSTEMS DICTATE THE LENGTHS PROVIDED.

Representative:	Customer:	Project:	Location:	Project Number:
-----------------	-----------	----------	-----------	-----------------

**50 MM WAY  
 PENDERGRASS, GA. 30567  
 PHONE: 706-824-7500  
 800-241-3460  
 FAX: 706-824-7501**

**www.mmsystemscorp.com**

For Spec-Data, Installation Guides, or movement requirements, contact MMSC

**RIGHTS OF DESIGN**

All rights of design, detail, engineering and/or invention contained herein are the property of MM Systems Corporation and hereby reserved and are not to be reproduced or provided to any other party. MM Systems Corporation reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

**VSS-2554-I**

Model:		
Drawn by:	Scale:	Drawing Number:
LMP	NTS	
SHT. . OF .	Issue Date:	
	12-22-14	