



ALUMINUM TRENCH FRAMES TO BE 6063-T5 ALLOY. COVER PLATE TO BE ARCHITECT SPECIFY 'PLAIN', 'ABRASIVE', 'DIAMOND PATTERN', OR 'PERFORATED'. FRAMES TO BE ANCHORED WITH 9361 ANCHORS SPACED 24" O.C. FURNISH END FRAMES WHERE SHOWN ON DRAWINGS. VINYL SEAL STRIP TO BE FURNISHED BETWEEN COVER PLATE AND FRAME. FORMED PAN LINER (IF REQUIRED) TO BE 20 GAUGE GALVANIZED STEEL (OR AS SPECIFIED).

GENERAL SPECIFICATIONS

STYLE:	TF-2812-R	PROJECT:	
MOVEMENT:		LOCATION:	
LINEAR FEET:		CUSTOMER:	
APPROVAL NOTE:		REPRESENTATIVE:	

50 MM WAY

PENDERGRASS, GA. 30567

PHONE: 706-824-7500

FAX: 706-824-7501



MM

MM SYSTEMS

APPROVAL NOTE:

- APPROVED AS SUBMITTED
- APPROVED AS NOTED

BY: _____
DATE: _____

REPRESENTATIVE:

SCALE:

DRAWN BY:

DATE:

JOB#:

REV #:

SHT. OF