



CRS SYSTEMS

SPECIAL DATA
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

DESCRIPTION

CRS systems consist of aluminum frame, centering bar, cover plate along with appropriate fasteners and anchors.

BASIC USE

CRS systems are used for covering expansion joint openings in walls and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Minimum sightline
- Accommodates seismic movement
- Recessed
- Aluminum (standard), bronze and stainless steel covers

FINISH

All exposed aluminum is normally a Clear Anodized finish. Other finishes are available.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- 204-R1 conforms to AA-M10C22A31.
- Conforms to ASTM E1399 for cycling joint.