VB-HD SERIES

SPEC DATA

MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

DESCRIPTION

VB-HD series consist of a side plate, center plate along with appropriate fasteners and anchors.

BASIC USE

VB-HD series are used for covering expansion joint openings and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Rugged heavy-duty to handle continuous pedestrian and wheel traffic.
- Blockout height is shallow.
- Shallow bevel, minimal bump design.
- ADA compliant
- Stainless steel and brass are available.

LIMITATIONS

Not for small sightlines due to its design.

FINISH

- Exposed surfaces are mill finish for aluminum systems
- Exposed surfaces are 304(2B) finish for stainless steel systems

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Stainless Steel conforms to ASTM A480 for sheet and plate.
- Conforms to ASTM E1399 for cycling joint.

MM Systems Corporation reserves the right to amend or withdraw information contained herein, without notice, and will not be liable for any inaccuracy or ambiguity of said information.

Current Issue: 05-21-15