



# EEHFX SYSTEMS

SPECC DATA  
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

## DESCRIPTION

EEHFX systems consist of aluminum frame, slide, along with appropriate fasteners and anchors.

## BASIC USE

EEHFX systems are used for covering expansion joint openings and providing a clean and aesthetically pleasing sightline where the joints occur.

## FEATURES

- Rugged heavy-duty to handle continuous pedestrian and heavy wheel traffic.
- For forklift loads up to 20,000 lbs.
- Minimal bump design.

## FINISH

All exposed aluminum is mill finish.

## STORAGE

All materials should be stored in a cool, dry location prior to use.

## INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation instructions.

## LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

## TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Conforms to ASTM E1399 for cycling joint.