



# LASDE SYSTEMS

**S P E C I D A T A**  
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

## DESCRIPTION

LASDE systems consist of aluminum frame, cover plate along with appropriate fasteners and anchors.

## BASIC USE

LASDE systems are used for covering expansion joint openings and providing a clean and aesthetically pleasing sightline where the joints occur.

## FEATURES

- Handle continuous pedestrian and light carts.
- Blockout height is shallow
- Minimum sightline

## LIMITATIONS

Not for forklift or heavy concentrated wheel loads.

## FINISH

All exposed aluminum is mill finish.

## STORAGE

All materials should be stored in a cool, dry location prior to use.

## INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation instructions.

## LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

## TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Conforms to ASTM E1399 for cycling joint.

MM Systems Corporation reserves the right to amend or withdraw information contained herein, without notice, and will not be liable for any inaccuracy or ambiguity of said information.

Current Issue: 12-10-04