



RSS & RWSS SYSTEMS

DESCRIPTION

RSS & RWSS systems consist of aluminum frame, Silicone outer seal, interior seal along with appropriate fasteners and anchors.

BASIC USE

RSS & RWSS systems are used for covering roof expansion joint openings, maintaining watertight integrity of the roof and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Protects from moisture and able to withstand multi-directional movement caused by wind, settling, thermal expansion or seismic activity.
- UV and fire resistant
- Color is available.

LIMITATIONS

Not designed for heavy concentrated loads.

FINISH

N/A

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation guide.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Conforms to ASTM E1399 for cycling joint.