



SX SYSTEMS

SPECIAL DATA
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

DESCRIPTION

SX systems are made up of frames and elastomeric joint filler (PVC).

BASIC USE

SX systems are used for covering expansion joint openings in walls and ceilings and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Installation is easy
- The seal is available in several colors

COLOR OPTIONS

Standard:

- Lunar
- Fog
- Carbon

FINISH

Aluminum frames are 204-R1 clear anodized.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop

drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- 204-R1 conforms to AA-M10C22A31.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399 for cycling joint.

MM Systems Corporation reserves the right to amend or withdraw information contained herein, without notice, and will not be liable for any inaccuracy or ambiguity of said information.

Current Issue: 08-18-05