



# VSG and VSGL SYSTEMS

## DESCRIPTION

VSG and VSGL systems are made up of frames and elastomeric joint filler.

## BASIC USE

VSG and VSGL systems are used for covering expansion joint openings in walls and ceilings and providing a clean and aesthetically pleasing sightline where the joints occur.

## FEATURES

- Installation is easy
- Seal can be installed later on most systems if necessary.
- The seal is available in many colors
- Wall systems may be fire rated.

## COLOR OPTIONS

Standard:

Lunar White, Prairie, Fog, Carbon

Non-Standard:

Heather, Madrid, Slate, Statuette

## FINISH

All exposed aluminum is mill finish.

## STORAGE

All materials should be stored in a cool, dry location prior to use.

## INSTALLATION

Apply to clean, dry, sound substrate. See manufacturer's standard installation instructions.

## LIMITED WARRANTY

MM Systems Corporation warrants materials

furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

## TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Santoprene conforms to:
  - ASTM D2240
  - ASTM D792
  - ASTM D412
  - ASTM D395
  - ASTM D624
  - ASTM D746
- Conforms to ASTM E1399 for cycling joint.