



VSL SYSTEMS

SPECIAL DATA
MM Systems Corp. • 50 MM Way, Pendergrass, GA 30567 • 800.241.3460 • www.mmsystemscorp.com

DESCRIPTION

The VSL series consist of aluminum exterior cover and interior frame along with a galvanized steel slide and base frame. Appropriate anchors are furnished.

BASIC USE

VSL series is used for covering expansion joint openings in walls. It providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Easy installation.
- The sightline blends into the surrounding wall when painted or other suitable wall covering is used.
- Maintenance free.

FINISH

Exterior aluminum cover is 204-R1 clear anodized.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any block-outs must be level before installation can begin. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date

of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Aluminum conforms to ASTM B209 for sheet and plate.
- Steel conforms to ASTM A569 for commercial quality sheet and plate.
- 204-R1 conforms to AA-M10C22A31.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399 for cycling joint.