



VSW and VSWL SYSTEMS

DESCRIPTION

VSW and VSWL systems are made up of frames and elastomeric seal.

BASIC USE

VSW and VSWL systems are used for covering expansion joint openings in walls and ceilings and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Installation is easy
- Seal can be installed later on most systems if necessary.
- The seal is available in many colors
- Wall systems may be fire rated.

COLOR OPTIONS

Standard:

Lunar White, Prairie, Fog, Carbon

Non-Standard:

Heather, Madrid, Slate, Statuette

FINISH

All exposed aluminum is mill finish.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. See manufacturer's standard installation instructions.

LIMITED WARRANTY

MM Systems Corporation warrants materials

furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Santoprene conforms to:
 - ASTM D2240
 - ASTM D792
 - ASTM D412
 - ASTM D395
 - ASTM D624
 - ASTM D746
- Conforms to ASTM E1399 for cycling joint.